MESSAGE NO: 8170113 MESSAGE DATE: 06/19/1998

MESSAGE STATUS: Active CATEGORY: Antidumping

TYPE: FNO-Final Det w/Order PUBLIC V NON-PUBLIC

SUB-TYPE:

FR CITE: FR FR CITE DATE:

REFERENCE MESSAGE #

(s):

CASE #(s): A-475-814

EFFECTIVE DATE: COURT CASE #:

PERIOD OF REVIEW: TO

PERIOD COVERED: 06/19/1998 TO

 Notice of Lifting of Suspension Date:

TO: { Directors Of Field Operations, Port Directors }

FROM: { Director AD/CVD & Revenue Policy & Programs }

RE: ANTIDUMPNG DUTY AMENDED ORDER IN THE INVESTIGATION OF CERTAIN SMALL DIAMETER SEAMLESS CARBON & ALLOY STEEL STANDARD LINE & PRESSSURE PIPE FROM ITALY (A-475-814)

MESSAGE NO: 8170113 DATE: 06 19 1998

CATEGORY: ADA TYPE: FNO REFERENCE: REFERENCE DATE:

CASES: A - 475 - 814 - -

_ _ _

- - -

PERIOD COVERED: 06 19 1998 TO

LIQ SUSPENSION DATE:

TO: CMC DIRECTORS, PORT DIRECTORS

FROM: DIRECTOR, IMPORT OPERATIONS

RE: ANTIDUMPNG DUTY AMENDED ORDER IN THE INVESTIGATION OF CERTAIN SMALL DIAMETER SEAMLESS CARBON & ALLOY STEEL STANDARD LINE & PRESSSURE PIPE FROM ITALY (A-475-814)

1. ON JUNE 10, 1998, THE DEPARTMENT OF COMMERCE PUBLISHED IN THE FEDERAL REGISTER ITS AMENDED ANTIDUMPING DUTY ORDER AND FINAL DETERMINATION IN THE INVESTIGATION OF CERTAIN SMALL DIAMETER SEAMLESS

CARBON AND ALLOY STEEL STANDARD, LINE AND PRESSURE PIPE FROM ITALY.
THIS IS AN AMENDMENT OF MESSAGE NUMBER 517111 ON JUNE 20, 1995.

2. THE SOCPE OF THIS INVESTIGATION INCLUDES SMALL DIAMETER SEAMLESS Message Date: 06/19/1998 Message Number: 8170113 Page 2 of 8

CARBON AND ALLOY STEEL STANDARD, LINE AND PRESSURE PIPES
(SEAMLESS PIPES) PRODUCED TO THE ASTM A-335, ASTMA-106, ASTM A-53 AND
API 5L SPECIFICATIONS AND MEETING THE PHYSICAL PARAMETERS DESCRIBED
BELOW, REGARDLESS OF APPLICATION. THE SCOPE OF THIS INVESTIGATION ALSO

INCLUDES ALL PRODUCTS USED IN STANDARD, LINE, OR PRESSURE PIPE APPLICATIONS AND MEETING THE PHYSICAL PARAMETERS BELOW, REGARDLESS OF

SPECIFICATION.

FOR PURPOSES OF THIS INVESTIGATION, SEAMLESS PIPES ARE SEAMLESS CARBON

AND ALLOY (OTHER THAN STAINLESS) STEEL PIPES, OF CIRCULAR CROSS-SECTION,

NOT MORE THAN 114.3 MM (4.5 INCHES) IN OUTSIDE DIAMETER, REGARDLESS OF WALL THICKNESS, MANUFACTURING PROCESS (HOT-FINISHED OR COLD-DRAWN), END

FINISH (PLAIN END, BEVELLED END, UPSET END, THREADED, OR THREADED AND COUPLED), OR SURFACE FINISH. THESE PIPES ARE COMMONLY KNOWN AS STANDARD PIPE, LINE PIPE OR PRESSURE PIPE, DEPENDING UPON THE APPLICATION. THEY MAY ALSO BE USED IN STRUCTURAL APPLICATIONS. PIPES PRODUCED IN NON-STANDARD WALL THICKNESSES ARE COMMONLY REFERRED TO AS

TUBES. THE SEAMLESS PIPES SUBJECT TO THIS INVESTIGATION ARE CURRENTLY

CLASSIFIABLE UNDER SUBHEADINGS 7304.10.10.20, 7304.10.50.20, 7304.31.60.50, 7304.39.00.16, 7304.39.00.20, 7304.39.00.24, 7304.39.00.28, 7304.39.00.32, 7304.51.50.05, 7304.51.50.60, 7304.59.60.00, 7304.59.80.10, 7304.59.80.15, 7304.59.80.20, AND 7304.59.80.25 OF THE HARMONIZED TARIFF SCHEDULE OF THE UNITED STATES (HTSUS). THE FOLLOWING INFORMATION FURTHER DEFINES THE SCOPE OF THIS INVESTIGATION, WHICH COVERS PIPES MEETING THE PHYSICAL PARAMETERS DESCRIBED ABOVE: SPECIFICATION CHARACTERISTICS AND USES: SEAMLESS PRESSURE PIPES ARE INTENDED FOR THE CONVEYANCE OF WATER, STEAM, PETROCHEMICALS, CHEMICALS, OIL PRODUCTS, NATURAL GAS AND OTHER LIQUIDS

AND GASSES IN INDUSTRIAL PIPING SYSTEMS. THEY MAY CARRY THESE
SUBSTANCES AT ELEVATED PRESSURES AND TEMPERATURES AND MAY BE SUBJECT
Message Date: 06/19/1998 Message Number: 8170113 Page 3 of 8

TO THE APPLICATION OF EXTERNAL HEAT. SEAMLESS CARBON STEEL PRESSURE

PIPE MEETING THE AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)
STANDARDA-106 MAY BE USED IN TEMPERATURES OF UP TO 1000 DEGREES
FAHRENHEIT. AT VARIOUS AMERICAN SOCIETY OF MECHANICAL ENGINEERS (ASME)

CODE STRESS LEVELS. ALLOY PIPES MADE TO ASTM STANDARD A-335 MUST BE USED IF TEMPERATURES AND TRESS LEVELS EXCEED THOSE ALLOWED FOR A-106

AND THE ASME CODES. SEAMLESS PRESSURE PIPES SOLD IN THE UNITED STATES

ARE COMMONLY PRODUCEDTO THE ASTM A-106STANDARD. SEAMLESS STANDARD

PIPESARE MOST COMMONLY PRODUCED TO THE ASTMA-53 SPECIFICATION AND

GENERALLY ARE NOT INTENDED FOR HIGH TEMPERATURE SERVICE. THEY ARE INTENDED FOR THE LOW TEMPERATUREAND PRESSURE CONVEYANCE OF WATER,

STEAM, NATURAL GAS, AIR AND OTHER LIQUIDS AND GASSES IN PLUMBING AND HEATING SYSTEMS, AIR CONDITIONING UNITS, AUTOMATIC SPRINKLER SYSTEMS, AND OTHER RELATED USES. STANDARD PIPES (DEPENDING ON TYPE AND CODE)

MAY CARRY LIQUIDS AT ELEVATED TEMPERATURES BUT MUST NOT EXCEED RELEVANT

ASME CODE REQUIREMENTS. SEAMLESS LINE PIPES ARE INTENDED FOR THE CONVEYANCE OF OIL AND NATURAL GAS OR OTHER FLUIDS IN PIPE LINES.

SEAMLESS LINE PIPES ARE PRODUCED TO THE API 5L SPECIFICATION. SEAMLESS PIPES ARE COMMONLY PRODUCED AND CERTIFIED TO MEET ASTM A-106, ASTM A-53

AND API 5L SPECIFICATIONS. SUCH TRIPLE CERTIFICATION OF PIPES IS COMMON BECAUSE ALL PIPES MEETING THE STRINGENT A-106 SPECIFICATION NECESSARILY

MEET THE API 5L AND ASTM A-53 SPECIFICATIONS. PIPES MEETING THE API 5L SPECIFICATION NECESSARILY MEET THE ASTM A-53 SPECIFICATION. HOWEVER, PIPES MEETING THE A-53 OR API 5L SPECIFICATIONS DO NOT NECESSARILY MEET THE A-106 SPECIFICATION. TO AVOID MAINTAINING SEPARATE PRODUCTION RUNS AND SEPARATE INVENTORIES, MANUFACTURES TRIPLE CERTIFY THE PIPES. SINCE Message Date: 06/19/1998 Message Number: 8170113 Page 4 of 8

DISTRIBUTORS SELL THE VAST MAJORITY OF THIS PRODUCT, THEY CAN THEREBY

MAINTAIN A SINGLE INVENTORY TO SERVICE ALL CUSTOMERS. THE PRIMARY
APPLICATION OF ASTMA-106 PRESSURE PIPES AND TRIPLE CERTIFIED PIPES IS IN
PRESSURE PIPING SYSTEMS BY REFINERIES, PETROCHEMICAL PLANTS AND CHEMICAL

PLANTS. OTHERAPPLICATIONS ARE IN POWER GENERATION PLANTS
(ELECTRICAL-FOSSIL FUEL OR NUCLEAR), AND IN SOME OIL FIELD USES (ON SHORE AND OFF SHORE) SUCH AS FOR SEPARATOR LINES, GATHERING LINES AND

METERING RUNS. A MINOR APPLICATION OF THIS PRODUCT IS FOR USE AS OIL AND GAS DISTRIBUTION LINES FOR COMMERCIAL APPLICATIONS. THESE APPLICATIONS CONSTITUTE THE MAJORITY OF THE MARKET FOR THE SUBJECT SEAMLESS PIPES. HOWEVER, A-106 PIPES MAY BE USED IN SOME BOILER APPLICATIONS. THE SCOPE OF THIS IVESTIGATION INCLUDES ALL SEAMLESS PIPE MEETING THE PHYSICAL PARAMETERS DESCRIBED ABOVE AND PRODUCED TO

ONE OF THE SPECIFICATIONS LISTED ABOVE, REGARDLESS OF APPLICATION, AND

WHETHER OR NOT ALSO CERTIFIED TO A NON-COVERED SPECIFICATION. STANDARD,

LINE AND PRESSURE APPLICATIONS AND THE ABOVE-LISTED SPECIFICATIONS ARE

DEFINING CHARACTERISTICS OF THE SCOPE OF THIS INVESTIGATION. THEREFORE,

SEAMLESS PIPES MEETING THE PHYSICAL DESCRIPTION ABOVE, BUT NOT PRODUCED

TO THE A-335, A-106, A-53,OR API 5L STANDARDS SHALL BE COVERED IF USED IN THE STANDARD, LINE OR PRESSURE APPLICATION. FOR EXAMPLE, THERE ARE CERTAIN OTHER ASTM SPECIFICATIONS OF PIPE WHICH, BECAUSE OF OVERLAPPING

CHARACTERISTICS, COULD POTENTIALLY BE USED IN A-106 APPLICATIONS. THESE SPECIFICATIONS GENERALLY INCLUDE A-162, A-192, A-210, A-333, AND A-524. WHEN SUCH PIPES ARE USED A STANDARD, LINE OR PRESSURE PIPE APPLICATION.

SUCH PRODUCTS ARE COVERED BY THE SCOPE OF THIS INVESTIGATION.

SPECIFICALLY EXCLUDED FROM THIS INVESTIGATION ARE BOILER TUBING AND Message Date: 06/19/1998 Message Number: 8170113 Page 5 of 8

MECHANICAL TUBING, IF SUCH PRODUCTS ARE NOT PRODUCED TO A-335, A-106, A-53 OR API 5L SPECIFICATIONS AND ARE NOT USED IN STANDARD, LINE OR PRESSURE APPLICATIONS. IN ADDITION, FINISHED AND UNFINISHED OCTG ARE EXCLUDED FROM THE SCOPE OF THIS INVESTIGATION. IF COVERED BY THE SCOPE

OF ANOTHER ANTIDUMPING DUTY ORDER FROM THE SAME COUNTRY. IF NOT COVERED BY SUCH AN OCTG ORDER, FINISHED AND UNFINISHED OCTG ARE INCLUDED IN THIS SCOPE WHEN USED IN STANDARD, LINE OR PRESSURE APPLICATIONS. FINALLY, ALSO EXCLUDED FROM THIS INVESTIGATION ARE REDRA WHOLLOWS FOR COLD-DRAWNING WHEN USED IN THE PRODUCTION OF

COLD-DRAWN PIPEOR TUBE. ALTHOUGH THE HTSUS SUBHEADINGS ARE PROVIDED FOR CONVENIENCE AND CUSTOMS PURPOSES, OUR WRITTEN DESCRIPTION OF THE SCOPE OF THIS INVESTIGATION IS DISPOSITIVE.

- 3. FOR FURTHER REPORTING PURPOSES THIS CASE HAS BEEN ASSIGNED INVESTIGATION NUMBER A-475-814.
- 4. FOR IMPORT OF CERTAIN SMALL DIAMETER SEAMLESS CARBON AND ALLOY STEEL STANDARD, LINE AND PRESSURE PIPE FROM ITALY, THE CUSTOMS SERVICE SHALL SUSPEND LIQUIDATION OF SUCH SHIPMENTS ENTERED OR WITHDRAWN FROM WAREHOUSE, FOR CONSUMPTION ON OR AFTER JUNE 19, 1995. EFFECTIVE AUGUST 3, 1995 CUSTOMS SHALL REQUIRE A CASH DEPOSIT EQUAL TO THE (MARGIN RATE)

MFR/PRODUCER CUSTOMS ID (MARGIN/AD VALOREM)
EXPORTER NUMBER PERCENTAGE RATE

DALMINE S.P.A. A-475-814-001 1.27%

ALL OTHER COMPANIES A-475-814-000 1.27%

SHOWN BELOW:

6. IF THERE ARE ANY QUESTIONS REGARDING THIS MATTER BY CUSTOMS OFFICE, Message Date: 06/19/1998 Message Number: 8170113 Page 6 of 8

PLEASE CONTACT VIA E-MAIL, THROUGH THE APPROPRIATE SUPERVISORY CHANNELS,

OTHER GOVERNMENT AGENCY LIAISON, USING THE ATTRIBUTE "HQ OAB." THE IMPORTING PUBLIC AND OTHER INTERESTED PARTIES SHOULD CONTACT KATHERINE

JOHNSON, OFFICE OF AD/CVD ENFORCEMENT, IMPORT ADMINISTRATION, INTERNATIONAL TRADE ADMINISTRATION, U.S. DEPARTMENT OF COMMERCE, AT (202) 482-4929.

7. THERE ARE NO RESTRICTIONS ON THE RELEASE OF THIS INFORMATION.

PAUL SCHWARTZ

Message Date: 06/19/1998 Message Number: 8170113 Page 7 of 8

Company Details

*Party Indicator Value:

I = Importer, M = Manufacturer, E = Exporter, S = Sold To Party

Message Date: 06/19/1998 Message Number: 8170113 Page 8 of 8